

MATERIAL SAFETY DATA SHEET

H M I S HAZARD RATINGS: Health 1 Flammability 0 Reactivity 0 Personal Protection B

SECTION I -- PRODUCT INFORMATION

MANUFACTURE'S NAME U.S. POLYCHEMICAL CORP MANUFACTURER'S CODE IDENTIFICATIONS: AC 600 COMPOSITE RESIN REMOVER
WEB SITE www.uspoly.com
STREET ADDRESS 584 CHESTNUT RIDGE ROAD CITY, STATE AND ZIP CODE CHESTNUT RIDGE, NY 10977
CHEMTREC TELEPHONE NO. 800-424-9300 PRODUCT CLASS AQUEOUS CLEANER
INFORMATION TELEPHONE NO. 845-356-5530 TRADE NAME POLYCHEM ACRASTRIP 600 CRR
TOLL FREE NUMBER 800-431-2072 PATENT NUMBER 5, 972, 865
FAX NUMBER 845-356-6656
PREPARATION DATE APRIL 17, 2002 REVISION DATE JANUARY, 2005 DATE ISSUED MAY 4, 2006

SECTION II -- HAZARDOUS INGREDIENTS

INGREDIENT	CAS NO.	%	OCCUPATIONAL EXPOSURE LIMITS				NIOSH/ OTHER
			OSHA		ACGIH		
			PEL/TWA PPM	PEL/CEILING PPM	TLV/TWA PPM	TLV/STEL PPM	
PROPYLENE GLYCOL METHYL ETHER ACETATE ALIPHATIC CARBOXYLIC ACID ESTERS, MIXTURE	108-65-6	--	N.E.	N.E.	N.E.	N.E.	--
	1119-40-0, 627-93-0, 106-65-0	--	N.E.	N.E.	N.E.	N.E.	--
	DPM * SEE SECTION IX N.E. = NOT ESTABLISHED	34590-94-8	--	100	150	100	150

The Acrastrip Formulation Is Accepted In Partnership With The
Design for the Environment ("DfE") Division Of The EPA



SECTION III -- PHYSICAL DATA

BOILING RANGE APPROXIMATELY: 212°F VAPOR DENSITY: () HEAVIER () LIGHTER THAN AIR () NOT APPLICABLE
EVAPORATION RATE: () FASTER () SLOWER THAN ETHER () NOT APPLICABLE
PERCENT VOLATILE BY VOLUME: CONCENTRATE: 62 VOC: CONCENTRATE: 620 g/l; HAPS, % NONE
IN 33% USE SOLUTION: 21 IN 33% USE SOLUTION: 207 g/l
SPECIFIC GRAVITY @ 20 °C 1.028 WEIGHT PER GALLON 8.6 LBS
SOLUBILITY IN WATER: SOLUBLE pH CONCENTRATE: 6.5-7.5 APPEARANCE AND ODOR: CLEAR SOLUTION, MILD ODOR

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: OSHA / DOT: UNCLASSIFIED FLASH POINT: NONE °F T.C.C LEL: NOT DETERMINED
EXTINGUISHING MEDIA (X) FOAM (X) ALCOHOL FOAM (X) CO₂ (X) DRY CHEMICAL (X) WATER FOG () OTHER
UNUSUAL FIRE AND EXPLOSION HAZARDS NONE KNOWN
SPECIAL FIRE FIGHTING PROCEDURES: NONE KNOWN.
COOL CONTAINERS WITH WATER SPRAY TO PREVENT RUPTURE.
POLYCHEM AC 600 COMPOSITE RESIN REMOVER

