

1 Identification

- **Product identifier**
- **Trade name:** *MONTANA GOLD Spray Paint all colors, fluo and shock*
- **Article number:**
283604 - 285844, 285899, 285905, 285929, 364945, 419331, 419348, 419355, 419362, 419379, 419386, 419393, 419409, 419416, 419423, 419430, 419447, 419454, 419461, 419478
- **Relevant identified uses of the substance or mixture and uses advised against --**
- **Application of the substance / the mixture** *Lacquer*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*MONTANA CANS
Häusserstr. 36
D-69115 Heidelberg
Tel. +49-6221-36333-30
Fax +49-6221-36333-33
info@montana-cans.de
www.montana-cans.com*
- **Information department:** *Abteilung Produktmanagement*
- **Emergency telephone number:**
*Tel.: +49 6266-75-310
Fax +49 6266-75-362
(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)*

2 Hazard(s) identification

- **Information concerning particular hazards for human and environment:**
*The product has to be labeled due to the calculation procedure of international guidelines.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Warning! Pressurized container.
Has a narcotizing effect.*
- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** *GHS02, GHS07, GHS08*
- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
titanium dioxide
- **Hazard statements**
*Extremely flammable aerosol. Pressurized container: May burst if heated.
Causes serious eye irritation.
Suspected of causing cancer.
May cause drowsiness or dizziness.*
- **Precautionary statements**
*If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Do not breathe spray.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents / container in accordance with local/regional/national/international regulations.*
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**
*Health = 1
Fire = 4
Reactivity = 3*

(Contd. on page 2)

USA

Printing date 02/27/2015

Reviewed on 02/27/2015

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 1)

- **HMIS-ratings (scale 0 - 4)**
- Health = 1
- Fire = 4
- Reactivity = 3
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 RTECS: PM 4780000 Reg.nr.: 01-2119472128-37	dimethyl ether F+ R12	12.5-<20%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 RTECS: AH 5425000 Reg.nr.: 01-2119475103-46	ethyl acetate Xi R36; F R11 R66-67	12.5-<20%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49	acetone Xi R36; F R11 R66-67	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 RTECS: TX 2275000 Reg.nr.: 01-2119486944-21	propane F+ R12	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 RTECS: EJ 4200000 Reg.nr.: 01-2119474691-32	butane F+ R12	5-<10%
CAS: 64742-94-5 EINECS: 265-198-5 Index number: 649-424-00-3 Reg.nr.: 01-2119510128-50	Solvent naphtha (petroleum), heavy arom. Xn R65	2.5-<5.0%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate R10	2.5-<5.0%

(Contd. on page 3)

USA

Printing date 02/27/2015

Reviewed on 02/27/2015

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

		(Contd. of page 2)
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 RTECS: ZE 2100000 Reg.nr.: 01-2119488216-32	xylene, mixture of isomers Xn R20/21; Xi R38 R10	2.5-<5.0%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 RTECS: TZ 4300000 Reg.nr.: 01-2119485395-27	isobutane F+ R12	<2.5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 RTECS: NT 8050000 Reg.nr.: 01-2119457558-25	propan-2-ol Xi R36; F R11 R67	<2.5%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons Xn R65; Xi R37; N R51/53 R10-66-67	<1.0%

Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply.
For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters -**

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow product to reach sewage system or any water course.
- **Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

USA

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

See Section 13 for disposal information.

(Contd. of page 3)

7 Handling and storage

- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Storage class:** 2B
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether	
WEEL	Long-term value: 1000 ppm
141-78-6 ethyl acetate	
PEL	Long-term value: 1400 mg/m ³ , 400 ppm
REL	Long-term value: 1400 mg/m ³ , 400 ppm
TLV	Long-term value: 1440 mg/m ³ , 400 ppm
67-64-1 acetone	
PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm
	BEI
74-98-6 propane	
PEL	Long-term value: 1800 mg/m ³ , 1000 ppm
REL	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV	refer to Appendix F
106-97-8 butane	
REL	Long-term value: 1900 mg/m ³ , 800 ppm
TLV	Short-term value: 2370 mg/m ³ , 1000 ppm
108-65-6 2-methoxy-1-methylethyl acetate	
WEEL	Long-term value: 50 ppm

(Contd. on page 5)

USA

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 4)

1330-20-7 xylene, mixture of isomers

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

75-28-5 isobutane

TLV Short-term value: 2370 mg/m³, 1000 ppm

67-63-0 propan-2-ol

PEL Long-term value: 980 mg/m³, 400 ppm

REL Short-term value: 1225 mg/m³, 500 ppm
Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 984 mg/m³, 400 ppm
Long-term value: 492 mg/m³, 200 ppm
BEI

· Ingredients with biological limit values:**67-64-1 acetone**

BEI 50 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

1330-20-7 xylene, mixture of isomers

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

67-63-0 propan-2-ol

BEI 40 mg/L
Medium: urine
Time: end of shift at end of workweek
Parameter: Acetone (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· Exposure controls**· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· Breathing equipment:

Filter AX
Not necessary if room is well-ventilated.

· Protection of hands:

Protective gloves
Solvent resistant gloves
In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves Butyl rubber, BR

(Contd. on page 6)

USA

Printing date 02/27/2015

Reviewed on 02/27/2015

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 5)

- **Penetration time of glove material**
Butyl rubber gloves with a thickness of 0.4 mm are resistant to:
Acetone: 480 min
Butyl acetate: 60 min
Ethyl acetate: 170 min
Xylene: 42 min
- **Eye protection:** Safety glasses

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
 - **Form:** Aerosol
 - **Color:** According to product specification
 - **Odor:** Characteristic
 - **Odour threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**
 - **Melting point/Melting range:** Undetermined.
 - **Boiling point/Boiling range:** Not applicable, as aerosol.
- **Flash point:** Not applicable, as aerosol.
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:** 235 °C (455 °F)
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not selfigniting.
- **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.
- **Explosion limits:**
 - **Lower:** 2.1 Vol %
 - **Upper:** 18.6 Vol %
- **Vapor pressure at 20 °C (68 °F):** 5200 hPa (3900 mm Hg)
- **Density at 20 °C (68 °F):** 0.96 g/cm³ (8.011 lbs/gal)
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not applicable.
- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - **Dynamic:** Not determined.
 - **Kinematic:** Not determined.
- **Solvent content:**
 - **VOC-USA** 62.2 %
652.0 g/l / 5.44 lb/gl
 - **Solids content:** 36.2 %
 - **Other information** No further relevant information available.

USA

(Contd. on page 7)

Printing date 02/27/2015

Reviewed on 02/27/2015

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 6)

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

141-78-6 ethyl acetate

Oral	LD50	5620 mg/kg (rabbit)
Inhalative	LC50/4 h	1600 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
Vapors have narcotic effect.

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
1330-20-7	xylene, mixture of isomers	3
67-63-0	propan-2-ol	3
7631-86-9	silicon dioxide, chemically prepared	3
100-41-4	ethylbenzene	2B
14808-60-7	Quartz (SiO ₂)	1
100-42-5	styrene	2B

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 8)

USA

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 7)

- **Additional ecological information:**
- **General notes:**
*Water hazard class 1 (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	UN1950
· DOT, ADR, IMDG, IATA	UN1950
· UN proper shipping name	Aerosols, flammable
· DOT	UN1950 Aerosols
· ADR	AEROSOLS
· IMDG	AEROSOLS, flammable
· IATA	AEROSOLS, flammable
· Transport hazard class(es)	
· DOT, IMDG, IATA	2.1
· Class	2.1
· Label	2.1
· ADR	2 5F Gases
· Class	2.1
· Label	
· Packing group	Void
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Gases
· Danger code (Kemler):	-
· EMS Number:	F-D,S-U
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	Code: E0
· Excepted quantities (EQ)	Not permitted as Excepted Quantity
· IMDG	
· Limited quantities (LQ)	1L

(Contd. on page 9)

USA

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 8)

- **Exempted quantities (EQ)** Code: E0
Not permitted as Exempted Quantity
- **UN "Model Regulation":** UN1950, Aerosols, 2.1

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture .**
- **Sara**

Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

1330-20-7	xylene, mixture of isomers
67-63-0	propan-2-ol
100-41-4	ethylbenzene
95-63-6	1,2,4-trimethylbenzene
98-82-8	cumene
85-44-9	phthalic anhydride
100-42-5	styrene

TSCA (Toxic Substances Control Act):

106-97-8	butane
141-78-6	ethyl acetate
67-64-1	acetone
74-98-6	propane
13463-67-7	titanium dioxide
64742-94-5	Solvent naphtha (petroleum), heavy arom.
108-65-6	2-methoxy-1-methylethyl acetate
9004-70-0	cellulose nitrate
67-63-0	propan-2-ol
7631-86-9	silicon dioxide, chemically prepared
100-41-4	ethylbenzene
64742-95-6	Solvent naphtha (petroleum), light arom.
95-63-6	1,2,4-trimethylbenzene
123-86-4	n-butyl acetate
108-67-8	mesitylene

Proposition 65

Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Cancerogenity categories

EPA (Environmental Protection Agency)

67-64-1	acetone
---------	---------

I

(Contd. on page 10)

USA

Printing date 02/27/2015

Reviewed on 02/27/2015

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 9)

1330-20-7	xylene, mixture of isomers	I
100-41-4	ethylbenzene	D
98-82-8	cumene	CBD

· TLV (Threshold Limit Value established by ACGIH)

67-64-1	acetone	A4
13463-67-7	titanium dioxide	A4
1330-20-7	xylene, mixture of isomers	A4
67-63-0	propan-2-ol	A4
100-41-4	ethylbenzene	A3
14808-60-7	Quartz (SiO ₂)	A2
85-44-9	phthalic anhydride	A4
100-42-5	styrene	A4

· MAK (German Maximum Workplace Concentration)

13463-67-7	titanium dioxide	3A
100-41-4	ethylbenzene	3A
14808-60-7	Quartz (SiO ₂)	I
100-42-5	styrene	5

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7	titanium dioxide	
14808-60-7	Quartz (SiO ₂)	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms GHS02, GHS07, GHS08

· Signal word Danger

· Hazard-determining components of labeling:

titanium dioxide

· Hazard statements

Extremely flammable aerosol. Pressurized container: May burst if heated.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe spray.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents / container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

* 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

R10 Flammable.

R11 Highly flammable.

R12 Extremely flammable.

(Contd. on page 11)

-USA-

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 10)

R20/21 Harmful by inhalation and in contact with skin.

R36 Irritating to eyes.

R37 Irritating to respiratory system.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· **Contact:** Anwendungstechnik

· **Date of preparation / last revision** 02/27/2015 / 3

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

USA